



**SKID STEER
TYRES**



-  EXCELLENT CUT AND CHIP RESISTANCE
-  LONGER TYRE LIFE
-  HEAVY DUTY APPLICATION

Skid Steer Tyres - ST 30

FEATURES:

ST 30 premium tyre is designed for heavy duty applications.

ADVANTAGES:

These tyres have a wide lug tread pattern that provides optimal grip and traction on both smooth and rough surfaces. The high quality tread compound promotes maximum tyre life and increased cut and chip resistance.

BENEFITS:

Excellent support to the equipment.



-  EXCELLENT CUT AND CHIP RESISTANCE
-  LONGER TYRE LIFE
-  OPTIMAL GRIP AND TRACTION

Skid Steer Tyres - ST 45 Plus

FEATURES:

ST 45 Plus is designed for general purpose along with rim guard

ADVANTAGES:

This tyre has a wide lug tread pattern that provides optimal grip and traction on both smooth and rough surfaces. The high quality tread compound promotes maximum tyre life and increased cut and chip resistance.

BENEFITS:

It offers cost efficiency, optimal grip and traction.



-  EXTRA TREAD LIFE
-  EXCELLENT DURABILITY
-  EXCELLENT HANDLING
-  RESISTANCE AGAINST SIDE IMPACTS
-  RESISTANCE TO PUNCTURE
-  GOOD TRACTION
-  LARGER FOOTPRINT

Skid Steer Tyres - ST 18

FEATURES:

It's non-directional with extra deep tread, large footprint with massive lug-to-void ratio, versatile tread pattern, wide sidewall.






ADVANTAGES:

It improves tread life & resistance against punctures, offers excellent durability and optimizes traction and handling on mixed & hard surfaces with superior side impact resistance

BENEFITS:

Enhanced durability and tread life.



-  LONGER TYRE LIFE
-  HEAVY DUTY APPLICATION
-  DURABILITY
-  REDUCED DOWNTIME
-  SUPERIOR TRACTION

Skid Steer Tyres - ST 27

FEATURES:

Premium skid steer tyre with deeper tread is designed for longer tyre life, heavy duty construction and reduced downtime.

ADVANTAGES:

Overlapping lugs with open shoulder is built for superior traction. Its heavy gauge sidewall with rim guard feature protects rim and reduces sidewall damage

BENEFITS:

Is developed to enhance protection of the wheel.



-  EXTRA PROTECTION AGAINST DAMAGE
-  INCREASED DURABILITY
-  SUPERIOR TRACTION

Skid Steer Tyres - ST 36

FEATURES:

ST 36 has been designed for reliable performance and quality. This reliable tyre solution is made to resist chunking and tearing.

ADVANTAGES:

Greater durability and traction. It's an ideal choice for light-duty, off-road skid steer loader application.

BENEFITS:

Excellent protection against damage.



-  EXCELLENT STABILITY
-  WEAR RESISTANCE
-  HIGH PUNCTURE RESISTANCE
-  EXTRA RESISTANCE AGAINST SIDE IMPACT
-  INCREASED DURABILITY
-  EXCELLENT GRIP

Skid Steer Tyres - IT 30

FEATURES:

The rubber compound is used to make the deep tread which provides unique wear resistance & increases the life span of the tyre. The bolstered up sidewalls improves stability and the hardened casing provides excellent stability and protection to the tyre from damage and punctures. This tyre range has been developed to deliver good performance at a competitive price for forklifts and other industrial equipment.

ADVANTAGES:

The reinforced sidewall, flat tread, and special compounding are built for longer tyre life and extra resistance against side impacts.

Premium choice for materials handling applications

BENEFITS:

Extended protection to the tyres.

SKID STEER TYRES

TECHNICAL DATA



Tyre Size	Pattern	Rim Width (inch)	Unloaded Inflated Dimensions ± 2%				Static Loaded Radius (mm)		Rolling Circumference (mm) ±2.5%		PR	LOAD INDEX	Type	Load Capacity (kg)						Inflation Pressure			
			SW (mm)		OD (mm)									8 (km/h)		16 (km/h)		25 (km/h)					
			mm	inch	mm	inch								kg	lbs	kg	lbs	kg	lbs			Kpa	psi
23x8.50-12	ST30 PLUS (IND)	7.00	215	8.5	575	22.6	262	10.3	1696	66.8	6	101 A2 / 93 A3	TL	820	1810	650	1435	599	1320	340	49		
														955	2105	755	1665	697	1535	440	64		
														1080	2380	855	1885	788	1740	540	78		
27x8.50-15	ST30	7.00	210	8.3	680	26.8	315	12.4	2007	79.0	6	109 A2 / 101 A3	TL	1030	2270	815	1795	752	1660	340	49		
														1250	2755	990	2185	913	2010	480	70		
27x10.5-15	ST30	8.50	260	10.2	700	27.6	323	12.7	2067	81.4	8	117 A2 / 108 A3	TL	1280	2820	1010	2225	934	2060	350	51		
														1560	3440	1235	2725	1139	2510	490	71		
31x15.5-15	ST30	13LB	390	15.4	810	31.9	369	14.5	2389	94.1	10	140 A2 / 131 A3	TL	2500	5515	1960	4320	1825	4025	420	61		
10-16.5	IT30	8.25	280	11.0	790	31.1	361	14.2	2331	91.8	10	134 A2 / 126 A3	TL	2135	4710	1685	3715	1559	3435	510	74		
	ST30													6	124 A2 / 116 A3	1590	3505	1255	2765	1161	2560	310	45
														8	130 A2 / 122 A3	1880	4145	1485	3275	1372	3025	410	59
														10	134 A2 / 126 A3	2135	4710	1685	3715	1559	3435	510	74
														8	130 A2 / 122 A3	1880	4145	1485	3275	1372	3025	410	59
	ST45 PLUS (IND)													10	134 A2 / 126 A3	2135	4710	1685	3715	1559	3435	510	74
	ST18													10	134 A2	2135	4710	1685	3715	1559	3435	510	74
	ST36													8	129 A2	1880	4145	1485	3275	1372	3025	410	59
ST27	10	134 A2	2135	4710	1685	3715	1560	3440	520	75													
12-16.5	IT30	9.75	330	13.0	835	32.9	377	14.9	2463	97.0	12	145 A2 / 137 A3	TL	2890	6370	2285	5040	2110	4650	560	81		
														14	147 A2 / 139 A3	3065	6760	2420	5335	2237	4935	620	90
	ST30										8	135 A2 / 126 A3		2180	4805	1720	3795	1591	3510	340	49		
														10	141 A2 / 132 A3	2540	5600	2010	4430	1854	4090	450	65
	ST30F										12	145 A2 / 137 A3		2890	6370	2285	5040	2110	4650	560	81		
														8	135 A2 / 126 A3	2180	4805	1720	3795	1591	3510	340	49
											10	141 A2 / 132 A3		2540	5600	2010	4430	1854	4090	450	65		
														12	145 A2 / 137 A3	2890	6370	2285	5040	2110	4650	560	81
	ST45 PLUS (IND)										10	141 A2 / 132 A3		2540	5600	2010	4430	1854	4090	450	65		
														12	145 A2 / 137 A3	2890	6370	2285	5040	2110	4650	560	81
	ST18										10	140 A2		2540	5600	2010	4430	1854	4090	450	65		
														12	145 A2	2890	6370	2285	5040	2110	4650	560	81
12		145 A2	2865	6315	2285	5040	2110	4655	550	80													
			10	140 A2	2540	5600	2010	4430	1854	4090	450	65											
31.5x13-16.5	ST30	9.75	325	12.8	795	31.3	363	14.3	2345	92.3	10	139 A2 / 131 A3	TL	2435	5370	1925	4245	1778	3920	480	70		
13.00		385	15.2	840	33.1	390	15.4	2537	99.9	12	148 A2 / 140 A3	TL	3145	6935	2485	5480	2296	5060	480	70			
14-17.5	ST30	10.50	360	14.2	945	37.2	427	16.8	2788	109.8	14	155 A2 / 147 A3	TL	3875	8545	3060	6745	2829	6235	550	80		
	ST27	10.50	393	15.5	934	37	416	16	2729	107.4	14	155 A2 / 147 A3	TL	3875	8545	3060	6745	2829	6235	550	80		
15-19.5	ST30	11.75	415	16.3	1020	40.2	461	18.2	3009	118.5	14	160 A2 / 153 A3	TL	4565	10065	3605	7950	3332	7350	485	70		
	ST27	11.75	433	17.0	1020	40.2	455	17.9	2981	117.3	14	160 A2 / 153 A3	TL	4565	10065	3605	7950	3332	7345	485	70		

TL- Tubeless